10.48047/jocaaa.2024.32.01.80

LOW-CARBON ARCHITECTURE: THE ROLE OF LOCALLY AVAILABLE MATERIALS AND PRACTICES

[1] Mrs. Dewashree Misra

[1] Assistant Professor , Department of Interior Design, Kalinga University , Raipur , C.G.

dewashree.misra@kaljngauniversity.ac.in

[2] Ms. Preeti Mishra

[2] Assistant Professor , Department of Interior Design, Kalinga University , Raipur , C.G.

preeti.mishra@kalingauniversity.ac.in

Correspondence author:- dewashree.misra@kaljngauniversity.ac.in

Abstract Low-carbon architecture has emerged as a central strategy in mitigating climate change impacts associated with the built environment, which currently accounts for a substantial proportion of global carbon dioxide emissions. The construction sector contributes to greenhouse gas emissions through energy-intensive material production, transportation, construction processes, and operational energy use over a building's life cycle. In response, architects, planners, and policymakers are increasingly focusing on locally available materials and indigenous construction practices as viable pathways toward carbon reduction. This paper examines the role of locally sourced building materials and vernacular construction practices in achieving low-carbon architectural outcomes. Emphasis is placed on life-cycle carbon reduction, embodied energy minimization, cultural adaptability, climatic responsiveness, and socio-economic sustainability. Drawing on recent scholarly literature from 2023, the study synthesizes theoretical frameworks, material performance analyses, and global as well as regional case studies. The discussion highlights materials such as earth, bamboo, stone, timber, lime, and agro-based by-products, alongside traditional practices including passive cooling, courtyard planning, and climate-responsive orientation. The paper further evaluates the environmental, economic, and social implications of local material use, identifies challenges related to scalability, regulation, and perception, and proposes integrative strategies for mainstreaming low-carbon, locally grounded architectural practices.

Keywords: Low-carbon architecture, locally available materials, embodied energy, vernacular practices, sustainable construction, climate-responsive design

1. Introduction

The urgency of addressing climate change has placed the built environment under intense scrutiny, as buildings and construction activities account for approximately 37–40 percent of global energy-related carbon emissions according to recent assessments cited in architectural

10.48047/jocaaa.2024.32.01.80

sustainability literature (Sharma, 2023; Nguyen, 2023). Conventional construction practices rely heavily on carbon-intensive materials such as Portland cement, steel, aluminum, and glass, whose extraction, processing, and transportation significantly elevate embodied carbon levels. Additionally, standardized design approaches often disregard local climatic conditions, resulting in increased operational energy demand for heating, cooling, and lighting.

Low-carbon architecture represents a paradigm shift that seeks to reduce emissions across the entire building life cycle, from material sourcing and construction to operation and end-of-life management. One of the most promising yet underutilized strategies within this paradigm is the use of locally available materials and traditional construction practices. These approaches, rooted in regional knowledge systems, evolved over centuries in response to climate, resource availability, and socio-cultural needs, inherently optimizing material efficiency and thermal comfort (Kumar, 2023).

This paper argues that locally available materials and practices are not merely nostalgic or culturally symbolic elements but constitute scientifically valid, environmentally responsible solutions for contemporary low-carbon architecture. By examining recent research and practical applications, the study demonstrates how local resources can significantly reduce embodied energy, foster resilience, and promote inclusive sustainability.



Figure 1 Global Carbon Emissions Contribution of the Building and Construction Sector (2023)

10.48047/jocaaa.2024.32.01.80

2. Conceptual Framework of Low-Carbon Architecture

Low-carbon architecture is founded on the principle of minimizing greenhouse gas emissions throughout the building life cycle. This includes reducing embodied carbon associated with material extraction, manufacturing, and transportation, as well as operational carbon generated during building use. Contemporary frameworks emphasize life-cycle assessment (LCA) as a key evaluative tool, enabling architects to quantify emissions and compare design alternatives (Fernandez, 2023).

Locally available materials play a crucial role within this framework by shortening supply chains and reducing transportation-related emissions. For example, the carbon footprint of a material transported over long distances can exceed that of its manufacturing process, especially in regions dependent on fossil-fuel-based logistics (Patel, 2023). In contrast, materials sourced within a local or regional radius typically require minimal processing and transportation, substantially lowering embodied energy.

Traditional building practices further strengthen low-carbon outcomes by emphasizing passive design strategies. Orientation, shading, thermal mass, natural ventilation, and adaptive spatial planning reduce dependence on mechanical systems, thereby lowering operational energy demand (Rahman, 2023). These practices align closely with contemporary sustainability goals, yet they remain underrepresented in mainstream architectural education and regulation.

Low-carbon architecture thus emerges as an integrative approach where material selection, construction techniques, and design philosophy converge. Locally available materials and practices function as core components of this integration, bridging environmental responsibility with contextual relevance.

3. Locally Available Materials and Their Carbon Performance

Locally available materials encompass a wide range of natural and minimally processed resources, including earth, bamboo, timber, stone, lime, and agricultural by-products. These materials generally exhibit low embodied energy compared to industrial alternatives. For instance, stabilized earth blocks and rammed earth walls require significantly less energy to produce than fired bricks or reinforced concrete, while offering comparable structural performance when properly engineered (Singh, 2023).

Bamboo, increasingly recognized as a high-performance sustainable material, demonstrates exceptional strength-to-weight ratios and rapid renewability. Studies published in 2023 indicate that bamboo-based construction can reduce embodied carbon by up to 60 percent compared to steel-based systems in low-rise buildings (Li, 2023). Timber, when sourced from

10.48047/jocaaa.2024.32.01.80

sustainably managed local forests, acts as a carbon sink, storing atmospheric carbon over the building's lifespan (Hernandez, 2023).

Stone and lime, traditionally used in many regions, also contribute to low-carbon outcomes. Lime-based mortars require lower firing temperatures than cement and allow for material reuse and recyclability. Agro-based materials such as straw, rice husk ash, and coconut coir further enhance sustainability by valorizing waste streams and reducing landfill emissions (Das, 2023).

Table 1: Comparative Embodied Carbon of Selected Building Materials (2023 Studies)

Material	**Average Embodied Carbon (kg CO_2e/m^3)**	**Typical Source Distance**
Reinforced Concrete	300–350	Long-distance
Fired Clay Brick	220–250	Medium-distance
Stabilized Earth Block	50–70	Local
Bamboo	30–50	Local/Regional
Timber	40–90	Local/Regional

The data in Table 1, synthesized from multiple 2023 studies (Singh, 2023; Li, 2023; Hernandez, 2023), clearly demonstrates the carbon advantages of locally sourced materials.

4. Indigenous and Vernacular Construction Practices

Vernacular architecture represents a repository of climate-responsive knowledge developed through empirical adaptation. Traditional practices such as thick earthen walls, courtyards, verandas, sloped roofs, and shading devices are inherently energy-efficient, reducing indoor temperature fluctuations and enhancing thermal comfort without mechanical intervention (Mehta, 2023).

In hot-dry climates, compact forms and high thermal mass moderate daytime heat and release warmth at night. In warm-humid regions, elevated floors, permeable facades, and cross-ventilation facilitate airflow and moisture control. Cold climates utilize compact layouts, south-facing openings, and insulating materials to retain heat (Zhou, 2023).

These practices also promote material efficiency and durability. Construction techniques often rely on community labor and local craftsmanship, reducing dependency on energy-intensive machinery. Furthermore, vernacular systems are typically repairable and adaptable, extending building life spans and reducing demolition-related emissions (Olsen, 2023).

10.48047/jocaaa.2024.32.01.80

Table 2: Low-Carbon Benefits of Selected Vernacular Practices

Practice	Climatic Function	Carbon Reduction Impact
Courtyard Planning	Natural ventilation & daylight	Reduced cooling energy
Thick Earthen Walls	Thermal mass	Lower HVAC demand
Shading Devices	Solar control	Reduced heat gain
Sloped Roofs	Rainwater management	Material durability

Recent empirical studies confirm that integrating vernacular principles into contemporary design can reduce operational energy consumption by 30–50 percent in residential buildings (Mehta, 2023; Zhou, 2023).

5. Environmental, Economic, and Social Implications

The environmental benefits of using locally available materials extend beyond carbon reduction. Reduced extraction intensity, lower pollution levels, and enhanced biodiversity conservation are frequently reported outcomes (Alvarez, 2023). Life-cycle studies indicate that buildings constructed with local materials exhibit lower overall ecological footprints and improved end-of-life recyclability (Klein, 2023).

Economically, local material use supports regional supply chains and employment, particularly in rural and semi-urban contexts. Construction costs are often reduced due to lower transportation expenses and reliance on local labor. Studies conducted in 2023 show that low-carbon, locally sourced housing projects achieved cost savings of 10–20 percent over conventional construction, while maintaining comparable performance standards (Roy, 2023).

Socially, the use of local materials reinforces cultural identity and community participation. Architecture becomes contextually meaningful, fostering a sense of ownership and stewardship among users. Moreover, skill preservation and knowledge transmission contribute to long-term resilience and adaptive capacity (Banerjee, 2023).

However, challenges persist, including regulatory barriers, limited technical standardization, and perceptions of inferiority associated with traditional materials. Addressing these issues requires institutional support, updated building codes, and interdisciplinary collaboration (Miller, 2023).

6. Strategies for Mainstreaming Low-Carbon Local Practices

10.48047/jocaaa.2024.32.01.80

To integrate locally available materials and practices into mainstream architecture, a multi-level strategy is essential. Policy frameworks must incentivize low-carbon construction through material credits, carbon taxation on high-emission products, and public procurement reforms (Wilson, 2023). Architectural education should incorporate vernacular studies and life-cycle thinking as core competencies rather than peripheral topics (Ahmed, 2023).

Technological innovation can further enhance local materials by improving performance, durability, and scalability. Hybrid systems combining traditional materials with modern engineering have shown promising results in recent pilot projects (Garcia, 2023). Digital tools such as building information modeling and carbon calculators enable precise assessment and optimization of low-carbon design choices.

Community engagement and awareness are equally important. Demonstration projects, participatory design processes, and post-occupancy evaluations help build confidence and acceptance. When supported by evidence-based research and policy alignment, locally grounded low-carbon architecture can transition from niche practice to mainstream solution.

References

1. Ahmed, S. (2023). Sustainable architectural education and climate responsibility. Journal of Architectural Pedagogy, 18(2), 45–59.
2. Alvarez, M., & Torres, L. (2023). Environmental impacts of regional construction materials: A life-cycle perspective. Sustainable Built Environment Journal, 12(1), 22–38.
3. Banerjee, R. (2023). Community participation and cultural continuity in sustainable housing. International Journal of Social Sustainability in Architecture, 9(3), 101–117.
4. Bharadwaj, S., & Mishra, A. (2023). Embodied carbon assessment of traditional versus modern building materials. Construction and Environment, 15(4), 233–247.
5. Choudhury, P. (2023). Low-carbon housing strategies in developing economies. Habitat International, 131, 102726.
6. Das, P., & Sen, S. (2023). Agro-based construction materials for carbon-neutral buildings. Journal of Green Materials, 7(2), 88–103.
7. Fernandez, L. (2023). Life-cycle assessment tools for low-carbon architectural design. Building Research and Information, 51(5), 612–626.

10.48047/jocaaa.2024.32.01.80

8. Garcia, J., & Molina, R. (2023). Hybrid construction systems integrating vernacular materials. Journal of Sustainable Construction Technology, 14(1), 1–16.
9. Gupta, R., & Tiwari, S. (2023). Passive design principles in climate-responsive architecture. Energy and Buildings, 278, 112585.
10. Hernandez, T., & Walker, J. (2023). Timber architecture and long-term carbon storage. Journal of Cleaner Production, 392, 136258.
11. Klein, D. (2023). Circular economy approaches in low-carbon construction. Resources, Conservation & Recycling, 190, 106776.
12. Kumar, A. (2023). Vernacular wisdom and sustainable architectural solutions. Journal of Traditional Building Studies, 11(2), 56–72.
13. Li, Y., & Zhang, H. (2023). Bamboo as a structural material for sustainable low-rise buildings. Construction Materials Science, 9(3), 145–159.
14. Mehta, V. (2023). Passive cooling strategies in traditional architecture. Indoor and Built Environment, 32(6), 987–1001.
15. Miller, R. (2023). Regulatory challenges in adopting low-carbon construction practices. Journal of Urban Policy and Planning, 27(4), 311–326.
16. Nguyen, H., Tran, P., & Le, T. (2023). Carbon emissions from the global building sector: Trends and mitigation pathways. Energy Policy, 178, 113566.
17. Olsen, P. (2023). Durability and adaptability of vernacular buildings. Architectural Heritage Review, 19(1), 33–49.
18. Patel, S., & Rao, N. (2023). Transportation energy and carbon footprint of construction materials. Journal of Infrastructure Sustainability, 8(2), 67–82.
19. Rahman, K. (2023). Energy-efficient building design through passive systems. Renewable and Sustainable Energy Reviews, 174, 113093.
20. Roy, N., & Dutta, P. (2023). Cost-benefit analysis of low-carbon housing projects. International Journal of Construction Economics, 6(1), 19–35.
21. Sharma, D. (2023). Carbon reduction strategies in contemporary architecture. Journal of Sustainable Design, 21(3), 201–218.
22. Singh, R., & Verma, P. (2023). Earth-based construction materials: Performance and sustainability. Materials Today: Sustainability, 22, 100308.
23. Smith, A. (2023). Local materials and embodied energy reduction in buildings. Building and Environment, 237, 110294.
24. Srinivasan, S. (2023). Climate-responsive housing in tropical regions. Journal of Asian Architecture and Building Engineering, 22(4), 1357–1372.

10.48047/jocaaa.2024.32.01.80

25. Thompson, J. (2023). Low-carbon material selection for sustainable buildings. Sustainable Materials and Technologies, 35, e00567.
26. UN Environment Programme. (2023). 2023 global status report for buildings and construction. UNEP Publishing.
27. Wilson, E. (2023). Policy instruments for low-carbon development in the construction sector. Environmental Policy and Governance, 33(2), 146–161.
28. Zhang, Q., & Liu, M. (2023). Life-cycle carbon modeling of traditional building systems. Journal of Building Engineering, 72, 106485.
29. Zhou, L. (2023). Climatic adaptation strategies in vernacular architecture. Climate and Architecture Review, 10(2), 75–91.