

A Comprehensive Review of Channel Estimation Challenges for 5G Massive MIMO

Parul Varshney

Department of Engineering & Technology
Shobhit Institute of Engineering & Technology, Meerut, India

R.K. Jain

Department of Engineering & Technology
Shobhit Institute of Engineering & Technology, Meerut, India

Abstract-As the wireless communication technology has advanced over the past few decades, Massive Multiple Input Multiple Output (M-MIMO) has emerged as a fundamental technology for the next generation mobile communication system. Achieving high spectral efficiency, reliability, and enhanced data rates in these systems strongly depends on accurate channel estimation. This paper gives a well organized review of the key challenges associated with channel estimation in Massive MIMO environments. It examines the different types of estimation techniques, including pilot-based, blind, semi-blind, and decision-directed methods. The main issue of pilot contamination and its effects on system performance is also described in detail. Furthermore, the review discusses emerging approaches such as deep learning-based channel estimation techniques. Finally, the study identifies existing research gaps and outlines potential future directions to enhance channel estimation performance in next-generation wireless networks.

Keywords- 5G, Massive MIMO, Channel Estimation, Pilot Contamination, CSI, ML. Deep Learning, 5G, IoT,

I. Introduction

The exponential growth in mobile internet usage and the proliferation of the Internet of Things (IoT) have created an urgent demand for high data rate wireless communication systems [30]. Emerging wireless technologies, commonly referred to as fifth-generation (5G) and beyond 5G (B5G) networks, are designed to address the increasing requirements of data-intensive applications by supporting massive user connectivity and significantly higher traffic volumes. Among the enabling technologies, massive multiple-input multiple-output (M-MIMO) has been widely recognized as a key solution for meeting these demands. By employing a large number of antennas at the base station (BS), M-MIMO systems can simultaneously serve multiple users, thereby improving system capacity, spectral efficiency, reliability, and overall network performance compared to conventional MIMO systems [40-41].

10.48047/jocaaa.2024.33.08.502

Despite its advantages, 5G technology faces several technical challenges that must be addressed for efficient deployment. One of the primary limitations in modern cellular networks is the reliance on increasing cell density and expanding available spectrum to achieve higher throughput. However, both approaches are constrained by physical and economic limitations, as spectrum resources are finite and dense network deployments result in increased latency, interference, and infrastructure costs. Consequently, alternative strategies focusing on improving spectral efficiency (SE) are essential to meet the growing demands of wireless communication systems.

Furthermore, next-generation networks are expected to deliver data rates up to 1000 times higher than previous generations. To achieve this, communication systems must operate in the millimeter-wave (mmWave) frequency bands (30–300 GHz), which offer wider bandwidth availability. However, mmWave communications suffer from severe path loss, necessitating the deployment of large antenna arrays to exploit spatial diversity and beamforming gains. In addition, the use of higher frequencies requires smaller cell sizes to mitigate interference and ensure reliable communication. In this context, M-MIMO emerges as a fundamental technology that enables efficient utilization of spatial resources while addressing the challenges associated with high-frequency propagation.

M-MIMO systems employ a large number of antenna elements at the BS, often exceeding hundreds, to enhance system performance. This large-scale antenna deployment significantly improves spectral efficiency, energy efficiency, and link robustness. By leveraging spatial multiplexing, a BS equipped with multiple antennas can simultaneously serve multiple user equipments (UEs) over the same time-frequency resources. Moreover, replacing conventional infrastructure expansion with large antenna arrays can reduce transmission power requirements through beamforming techniques tailored for M-MIMO systems [9]. Additionally, the availability of higher degrees of freedom enables efficient spatial resource allocation, further enhancing spectral efficiency [18].

Although M-MIMO offers substantial benefits, several critical challenges hinder its practical implementation. Key issues include signal detection complexity, pilot contamination, and accurate channel estimation, which significantly impact system performance [49]. Among these, channel estimation remains one of the most challenging problems due to the high dimensionality and dynamic nature of wireless channels in M-MIMO systems.

This paper presents a comprehensive survey of recent advancements in channel estimation techniques for M-MIMO systems. It provides a detailed conceptual understanding of the associated challenges and discusses state-of-the-art solutions reported in the literature. The study aims to assist researchers in identifying effective approaches for integrating M-MIMO into 5G systems.



Challenges in Massive MIMO deployment

In this study, a systematic review methodology has been adopted and total of research papers published between 2002 and 2026 were analyzed.


The review focuses on:

- Conventional channel estimation techniques
- Issues in Massive MIMO systems
- Pilot contamination problem
- Advanced machine learning approaches

The techniques are categorized into:

1. Pilot-Based Channel Estimation (PBCE)
2. Blind Channel Estimation (BCE)
3. Semi-Blind Channel Estimation (SBCE)
4. Decision-Directed Channel Estimation (DDCE)

II. Channel Estimation Techniques



3.1 Pilot-Based Channel Estimation (PBCE)

Pilot-based channel estimation techniques are highly effective as long as the pilot signals used within a cell and its neighboring cells remain mutually orthogonal. However, in practical wireless systems, there is a strict limitation on the number of orthogonal pilot sequences that can be accommodated within a given bandwidth and coherence time. Due to this limitation, the same pilot sequences must often be reused across adjacent cells. This reuse leads to interference when neighboring cells transmit identical pilot signals simultaneously. Consequently, the base station (BS) receives a superimposed signal containing channel information not only from its own users but also from users in surrounding cells. This

10.48047/jocaaa.2024.33.08.502

phenomenon is known as **pilot contamination (PC)**, and it significantly degrades the accuracy of channel estimation, ultimately limiting the achievable data rates .

The impact of pilot contamination becomes even more severe during downlink transmission. While the BS uses beamforming techniques to direct signals toward intended users within its own cell, the contaminated channel estimates cause unintended signal leakage toward users in neighboring cells. This results in intercell interference, reducing overall system efficiency and reliability. Although pilot reuse was introduced as a method to improve spectral efficiency, it inadvertently intensifies these interference issues.

In addition to pilot contamination, pilot-based estimation suffers from inefficient utilization of channel capacity, as a portion of the available resources must always be reserved for transmitting pilot signals instead of actual data. Furthermore, the dependence on interpolation techniques to estimate channel variations introduces additional inaccuracies, since these methods cannot perfectly reconstruct the channel conditions. Overall, the reliance on pilots, combined with reuse strategies and imperfect estimation methods, leads to significant performance degradation in Massive MIMO systems. Therefore, mitigating pilot contamination through advanced pilot decontamination techniques has become a crucial area of research to improve channel estimation accuracy and system performance.

3.2 Blind Channel Estimation (BCE)

Blind channel estimation techniques rely on the inherent information embedded within the received signals to estimate the communication channel, eliminating the need for explicit pilot sequences. By analyzing the structural and statistical properties of the transmitted signals, the receiver can infer channel characteristics, thereby avoiding issues such as pilot contamination. However, in Massive MIMO systems, especially for downlink transmission, traditional blind methods—such as Independent Component Analysis (ICA), subspace-based techniques, and covariance reduction methods—are generally unsuitable, as they are primarily designed for uplink channel estimation rather than downlink scenarios .

In Time Division Duplexing (TDD)-based multiuser Massive MIMO systems, the complexity of downlink channel estimation can instead be reduced to estimating the **downlink channel gain**, often with the help of appropriate precoding techniques. A commonly used approach is to compute the average channel gain; however, this method suffers from significant

10.48047/jocaaa.2024.33.08.502

estimation errors and depends heavily on prior knowledge of channel statistics. To overcome these limitations, more advanced blind techniques have been proposed, where the base station precodes user signals using methods such as Maximum Ratio (MR) or Zero-Forcing (ZF), based on uplink channel estimates. These precoded signals are then transmitted to mobile stations, where each receiver estimates the channel gain by measuring the average power of the received signal, which is subsequently used for signal detection.

For uplink channel estimation, a variety of blind methods are employed, including Singular Value Decomposition (SVD)-based techniques, Maximum A Posteriori (MAP) estimation, diagonal jacket matrix approaches combined with Iterative Least Squares with Projection (ILSP), and expectation propagation methods. Additionally, covariance-based estimation techniques aim to mitigate pilot contamination by exploiting the fact that desired signals and interference often occupy different subspaces. Spatial-domain approaches further enhance estimation by utilizing properties such as angle of arrival and temporal characteristics of the channel. Other strategies, including optimized pilot assignment, multi-cell Minimum Mean Square Error (MMSE) precoding, and pilot contamination precoding, have also been proposed to reduce interference effects. Despite these advancements, the major limitation of blind channel estimation techniques remains their relatively lower accuracy, which can degrade both uplink and downlink communication performance.

3.3 Semi-Blind Channel Estimation (SBCE)

Semi-blind channel estimation (SBCE) is an advanced technique that improves the accuracy of channel coefficient estimation by combining both **known pilot (training) data** and the **information embedded in unknown data symbols**. Unlike purely pilot-based methods, SBCE leverages the additional structure present in transmitted data to refine channel estimates, thereby enhancing overall performance. One of its key advantages is flexibility: it allows system designers to either achieve higher estimation accuracy using the same number of pilot symbols or maintain similar accuracy while reducing pilot overhead, which improves spectral efficiency.

In Frequency Division Duplexing (FDD) systems, improved channel estimation directly enhances the receiver's ability to correctly detect unknown data symbols. In Time Division Duplexing (TDD) systems, where uplink and downlink channels are assumed to be

10.48047/jocaaa.2024.33.08.502

reciprocal, better channel estimates provide dual benefits: they improve uplink signal detection and enable the base station (BS) to design more accurate and efficient downlink precoding strategies. Since Massive MIMO systems predominantly rely on TDD operation due to its scalability and reduced overhead, semi-blind channel estimation becomes particularly valuable. By improving both uplink and downlink performance while reducing dependence on pilot signals, SBCE emerges as a promising solution for next-generation wireless communication systems, especially in large-scale antenna deployments.

3.4 Decision-Directed Channel Estimation (DDCE)

Decision-Directed Channel Estimation (DDCE) is a technique developed to address the limitations of traditional pilot-assisted channel estimation methods in rapidly time-varying wireless environments. Conventional approaches typically assume a quasi-static fading channel, where the channel remains constant over a block of symbols; however, this assumption breaks down in high-mobility scenarios where the channel changes quickly and the coherence time is very short. To overcome this, DDCE introduces a dynamic and adaptive framework in which an initial set of pilot symbols is first transmitted to obtain a preliminary estimate of the Channel State Information (CSI). Following this, during data transmission, the receiver treats the detected data symbols as additional training data and continuously updates and refines the channel estimate, enabling real-time tracking and prediction of channel variations .

A key feature of DDCE is its reliance on **channel prediction**, where future channel states are estimated based on past observations. This prediction process commonly uses techniques such as the Wiener filter, finite-length Wiener filter, and recursive least squares methods like the Kalman filter. However, the effectiveness of these predictors depends heavily on accurate knowledge of channel statistics, particularly the Doppler rate, which reflects the speed of channel variation. In high-mobility scenarios—such as vehicular communications (e.g., IEEE 802.11p systems)—estimating the Doppler rate accurately is extremely challenging. Any inaccuracies in this estimation can lead to significant error propagation, especially when using sensitive predictors like the Kalman filter, thereby degrading overall system performance.

To address these limitations, recent research has explored the application of deep learning (DL) techniques in channel estimation. Deep Neural Networks (DNNs) offer the ability to learn complex, nonlinear channel behaviors directly from data without requiring precise

10.48047/jocaaa.2024.33.08.502


mathematical models. This is particularly advantageous because real-world wireless channels often exhibit irregularities and impairments that are difficult to model analytically. By leveraging data-driven learning, deep learning-based approaches can improve prediction accuracy and robustness in highly dynamic environments. Nevertheless, despite these advancements, DDCE techniques still face challenges due to their dependence on model accuracy and their sensitivity to estimation errors, making it difficult to fully capture the complex nature of fast-varying wireless channels.

4.1 Major Challenges Identified

- Pilot contamination due to reuse of pilot signals
- High computational complexity with large antenna arrays
- Limited spectral efficiency
- Inter-cell interference
- Channel variability in high mobility scenarios

4.2 Impact of Pilot Contamination

Pilot contamination significantly degrades system performance by introducing interference from neighboring cells. This affects both uplink and downlink communication. Pilot contamination gives birth to difficult signal detection as well wastages of bandwidth.



4.3 Role of Deep Learning

Deep learning models such as DNNs are emerging as powerful tools for channel estimation. DNN makes use of(convolution)and RNN(recurrent) as an underlying layer. An unified DNN can be used for all channel scenarios unlike conventional channel estimation techniques. They can learn complex channel characteristics without requiring exact mathematical models.

IV. Discussion

The review indicates that no single channel estimation technique is universally optimal. Pilot-based methods are simple but suffer from interference, while blind methods reduce overhead but lack accuracy.

Hybrid approaches, such as semi-blind estimation, provide a balanced solution. Furthermore, deep learning-based techniques show promising results in handling non-linear and complex channel conditions.

V. Conclusion

This paper presents a comprehensive review of channel estimation challenges in Massive MIMO systems for 5G communication. Pilot contamination remains the most critical issue affecting system performance.

Future research should focus on:

- Efficient pilot allocation strategies
- Low-complexity estimation algorithms
- AI-based channel estimation methods
- Robust solutions for high mobility scenarios

Accurate channel estimation will play a crucial role in achieving reliable and high-speed communication in future wireless networks.

References

10.48047/jocaaa.2024.33.08.502

- [1] Sufyan, A.; Khan, K.B.; Khashan, O.A.; Mir, T.; Mir, U. From 5G to beyond 5G: A Comprehensive Survey of Wireless Network Evolution, Challenges, and Promising Technologies. *Electronics* 2023, 12, 2200
- [2] Patrudu, B.C.K.; Sridevi, P. Comparison of Uplink Spectral Efficiency in Massive MIMO Systems. In *Intelligent Computing in Control and Communication*; Springer: Berlin/Heidelberg, Germany, 2021; pp. 13–22.
- [3] Dicandia, F.A.; Genovesi, S. Exploitation of triangular lattice arrays for improved spectral efficiency in massive MIMO 5G systems. *IEEE Access* 2021, 9, 17530–17543.
- [4] Lu, A.A.; Gao, X.; Meng, X.; Xia, X.G. Omnidirectional Precoding for 3D Massive MIMO with Uniform Planar Arrays. *IEEE Trans. Wirel. Commun.* 2020, 19, 2628–2642.
- [5] M. H. Alsharif, A. H. Kelechi, M. A. Albreem, S. A. Chaudhry, M. S. Zia, and S. Kim, “Sixth Generation (6G) Wireless Networks: Vision, Research Activities, Challenges and Potential Solutions,” *Symmetry*, vol. 12, no. 4, p. 676, Apr. 2020.
- [6] Azeem, H.; Du, L.; Ullah, A.; Mughal, M.A.; Aslam, M.M.; Ikram, M. Sub-array Based Antenna Selection Scheme for Massive MIMO in 5G. In *Cyberspace Data and Intelligence, and Cyber-Living, Syndrome, and Health*; Springer: Berlin/Heidelberg, Germany, 2019; pp. 38–50.
- [7] Mir, T.; Siddiqi, Z.; Mir, U.; MacKenzie, R.; Hao, M. One-Bit Hybrid Precoding for Wideband Millimeter-Wave Massive MIMO Systems. In Proceedings of the 2019 IEEE 89th Vehicular Technology Conference (VTC2019-Spring), Kuala Lumpur, Malaysia, 28 April–1 May 2019; pp. 1–6.
- [8] Okyere, B.; Musavian, L.; Mumtaz, R. Multi-User Massive MIMO and Physical Layer Network Coding. In Proceedings of the 2019 IEEE Globecom Workshops (GC Wkshps), Waikoloa, HI, USA, 9–13 December 2019; pp. 1–6.
- [9] Akhlaghpasand, H.; Björnson, E.; Razavizadeh, S.M. Jamming Suppression in Massive MIMO Systems. *IEEE Trans. Circuits Syst. II Express Briefs* 2019, 67, 182–186.
- [10] Al-nahari, A.; Sakran, H.; Su, W.; Tarbosh, S. Energy and spectral efficiency of secure massive MIMO downlink systems. *IET Commun.* 2019, 13, 1364–1372.
- [11] M. Mohammadkarimi, M. Mehrabi, M. Ardakani, and Y. Jing, “Deep learning based sphere decoding,” *IEEE Transactions on Wireless Communications*, Accepted for publication, 2019.

10.48047/jocaaa.2024.33.08.502

- [12] Hasan, W.B.; Harris, P.; Bromell, H.; Doufexi, A.; Beach, M. Adaptive User Grouping Based on EVM Prediction for Efficient & Robust Massive MIMO in TDD. *IEEE Access* 2019, 7, 162683–162696.
- [13] Pandey, B.C.; Mohammed, S.K. A Low-Latency Transmission Method for Massive MIMO Systems with Low Control Signalling Overhead. *IEEE Trans. Commun.* 2019, 67, 3292–3308.
- [14] Albreem, M.A.; Juntti, M.; Shahabuddin, S. Massive MIMO detection techniques: a survey. *IEEE Commun. Surv. Tutor.* 2019, 21, 3109–3132.
- [15] Jedda, H.; Nossek, J.A. On PAPR in Single-Carrier Massive MIMO Systems. In Proceedings of the WSA 2019; 23rd International ITG Workshop on Smart Antennas, Vienna, Austria, 24–26 April 2019; pp. 1–5.
- [16] Björnson, E., Sanguinetti, L.: Making cell-free massive MIMO competitive with MMSE processing and centralized implementation. *IEEE Trans. Wireless Commun.* 19(1), 77–90 (2019)
- [17] Shlezinger, N.; Eldar, Y.C. Spectral Efficiency of Noncooperative Uplink Massive MIMO Systems with Joint Decoding. In Proceedings of the ICASSP 2019–2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Brighton, UK, 12–17 May 2019; pp. 4779–4783.
- [18] Busari, S.A.; Huq, K.M.S.; Mumtaz, S.; Rodriguez, J. Terahertz massive MIMO for beyond-5G wireless communication. In Proceedings of the ICC 2019–2019 IEEE International Conference on Communications (ICC), Shanghai, China, 20–24 May 2019.
- [19] H. Ye, G. Y. Li, and B.-H. Juang, “Power of deep learning for channel estimation and signal detection in OFDM systems,” *IEEE Wireless Communications Letters*, vol. 7, no. 1, pp. 114–117, 2018.
- [20] E. Nachmani, E. Marciano, L. Lugosch, W. J. Gross, D. Burshtein, and Y. Be’ery, “Deep learning methods for improved decoding of linear codes,” *IEEE Journal of Selected Topics in Signal Processing*, vol. 12, no. 1, pp. 119–131, Feb 2018.
- [21] N. Farsad and A. Goldsmith, “Neural network detection of data sequences in communication systems,” *IEEE Transactions on Signal Processing*, vol. 66, no. 21, pp. 5663–5678, Nov 2018.
- [22] M. Kim, N. Kim, W. Lee, and D. Cho, “Deep learning-aided SCMA,” *IEEE Communications Letters*, vol. 22, no. 4, pp. 720–723, April 2018.

10.48047/jocaaa.2024.33.08.502

- [23] S. Dörner, S. Cammerer, J. Hoydis, and S. t. Brink, “Deep learning based communication over the air,” *IEEE Journal of Selected Topics in Signal Processing*, vol. 12, no. 1, pp. 132–143, Feb 2018.
- [24] T. Erpek, T. J. O’Shea, and T. C. Clancy, “Learning a physical layer scheme for the MIMO interference channel,” in *2018 IEEE International Conference on Communications (ICC)*, May 2018, pp. 1–5.
- [25] H. He, C. Wen, S. Jin, and G. Y. Li, “Deep learning-based channel estimation for beamspace mmWave massive MIMO systems,” *IEEE Wireless Communications Letters*, vol. 7, no. 5, pp. 852–855, Oct 2018.
- [26] Muppirisetty LS, Charalambous Th, Karout J, Fodor G, Wymeersch H. Locationaided pilot contamination avoidance for massive MIMO systems. *IEEE Trans. Wireless Commun.* 2018;17(4):2662–74.
- [27] T. O’Shea and J. Hoydis, “An introduction to deep learning for the physical layer,” *IEEE Transactions on Cognitive Communications and Networking*, vol. 3, no. 4, pp. 563–575, Dec 2017.
- [28] Ngo HQ, Larsson EG. No downlink pilots are needed in TDD massive MIMO. *IEEE Trans. Wireless Commun.* 2017;16(5):2921–35.
- [29] T. J. O’Shea, T. Erpek, and T. C. Clancy, “Physical layer deep learning of encodings for the MIMO fading channel,” in *2017 55th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, Oct 2017, pp. 76–80.
- [30] Xiang, W.; Zheng, K.; Shen, X.S. *5G Mobile Communications*; Springer International Publishing: Basel, Switzerland, 2017.
- [31] Busari, S.A., et al.: Millimeter-wave massive MIMO communication for future wireless systems: A survey. *IEEE Commun. Surv. Tutor.* 20, 836–869 (2017)
- [32] N. Hassan and X. Fernando, “Massive MIMO Wireless Networks: An Overview,” *Electronics*, vol. 6, no. 3, p. 63, Sep. 2017.
- [33] Björnson, E.; Hoydis, J.; Sanguinetti, L. Massive MIMO networks: Spectral, energy, and hardware efficiency. *Found. Trends Signal Process.* 2017, 11, 154–655.
- [34] Xu, C.; Hu, Y.; Liang, C.; Ma, J.; Ping, L. Massive MIMO, non-orthogonal multiple access and interleave division multiple access. *IEEE Access* 2017, 5, 14728–14748.

10.48047/jocaaa.2024.33.08.502

- [35] H. PAPADOPOULOS, C. WANG, O. BURSALIOGLU, X. HOU, and Y. KISHIYAMA, "Massive MIMO Technologies and Challenges towards 5G," *IEICE Transactions on Communications*, vol. E99.B, no. 3, pp. 602–621, 2016.
- [36] I. Goodfellow, Y. Bengio, A. Courville, and Y. Bengio, *Deep learning*. MIT press Cambridge, 2016, vol. 1.
- [37] E. Björnson, E. G. Larsson, and T. L. Marzetta, "Massive MIMO: ten myths and one critical question," *IEEE Communications Magazine*, vol. 54, no. 2, pp. 114–123, Feb. 2016.
- [38] Zhang, Z.; Chai, X.; Long, K.; Vasilakos, A.V.; Hanzo, L. Full duplex techniques for 5G networks: self-interference cancellation, protocol design, and relay selection. *IEEE Commun. Mag.* 2015, 53, 128–137.
- [39] M. Teeti, J. Sun, D. Gesbert, and Y. Liu, "The Impact of Physical Channel on Performance of SubspaceBased Channel Estimation in Massive MIMO Systems," *IEEE Transactions on Wireless Communications*, vol. 14, no. 9, pp. 4743–4756, Sep. 2015.
- [40] Lu, L.; Li, G.Y.A.; Swindlehurst, L.; Ashikhmin, A.; Zhang, R. An overview of massive MIMO: Benefits and challenges. *IEEE J. Sel. Topics Signal Process.* 2014, 8, 742–758.
- [41] Wu, M.; Yin, B.; Wang, G.; Dick, C.; Cavallaro, J.R.; Studer, C. Large-scale MIMO detection for 3GPP LTE:algorithms and FPGA implementations. *IEEE J. Sel. Topics Signal Process.* 2014, 8, 916–929.
- [42] M. Latif Sarker, M.H. Lee, A fast channel estimation and the reduction of pilot contamination problem for massive MIMO based on a diagonal jacket matrix, in: Proc. 4th Int. Workshop Fiber Opt. Access Netw. (FOAN), 2013, pp. 26–30.
- [43] E. G. Larsson, O. Edfors, F. Tufvesson, and T. L. Marzetta, "Massive MIMO for next generation wireless systems," *IEEE Communications Magazine*, vol. 52, no. 2, pp. 186–195, Feb. 2014.
- [44] Ngo, H.; Larsson, E.; Marzetta, T. Energy and spectral efficiency of very large multiuser MIMO systems. *IEEE Trans. Commun.* 2012, 61, 1436–1449.
- [45] Jose J, Ashikhmin A, Marzetta T, Vishwanath S. Pilot contamination and precoding in multi-cell TDD systems. *IEEE Trans. Wireless Commun.* 2011;10 (8):2640–51.
- [46] A. Ashikhmin, T. Marzetta, Pilot contamination precoding in multicell large scale antenna systems, in: Proc. IEEE Int. Symp. Inf. Theory (ISIT), 2012, pp. 1137–1141

10.48047/jocaaa.2024.33.08.502

- [47] Jose, J.; Ashikhmin, A.; Marzetta, T.; Vishwanath, S. Pilot contamination and precoding in multi-cell TDD systems. *IEEE Trans. Wireless Commun.* 2011, 10, 2640–2651.
- [48] O. Oyerinde and S. Mneney, “Review of channel estimation for wireless communication systems,” *IETE Technical Review*, vol. 29, no. 4, p. 282, 2012.
- [49] 3GPP TR 36.814, V9.0.0, 2010, Further Advancements for E-UTRA Physical Layer Aspects, March 2010
- [50] Marzetta, T.L. Noncooperative cellular wireless with unlimited numbers of base station antennas. *IEEE Trans. Wirel. Commun.* 2010, 9, 3590–3600.
- [51] T. L. Marzetta, “Noncooperative Cellular Wireless with Unlimited Numbers of Base Station Antennas,” *IEEE Transactions on Wireless Communications*, vol. 9, no. 11, pp. 3590-3600, Nov. 2010.
- [52] F. Rusek *et al.*, “Scaling up MIMO: Opportunities and challenges with very large arrays,” *IEEE Signal Process. Mag.*, vol. 30, no. 1, pp. 40–60, Jan. 2013.
- [53] Gopalakrishnan, B.; Jindal, N. An analysis of pilot contamination on multi-user MIMO cellular systems with many antennas. In Proceedings of the IEEE 12th International Workshop on Signal Processing Advances in Wireless Communications (SPAWC), San Francisco, CA, USA, 26–29 June 2011; pp. 381–385.
- [54] Krishnan, N.; Yates, R.; Mandayam, N. Cellular systems with many antennas: Large system analysis under pilot contamination. In Proceedings of the 50th Annual Allerton Conference on Communication, Control, and Computing (Allerton), Monticello, IL, USA, 1–5 October 2012; pp. 1220–1224.
- [55] A. Petropulu, R. Zhang, and R. Lin, “Blind OFDM Channel Estimation Through Simple Linear Precoding,” *IEEE Transactions on Wireless Communications*, vol. 3, no. 2, pp. 647–655, Mar. 2004.
- [56] Shen L, Yao Y, Wang H, Wang H. Blind decoding based on independent component analysis for a massive MIMO uplink system in microcell Rician/ Rayleigh fading channels. *IEEE Trans. Veh. Technol.* 2016;56(10):8322–9.
- [57] Shin C, Heath RW, Powers EJ. Blind channel estimation for MIMO-OFDM systems. *IEEE Trans. Veh. Technol.* 2007;56(2):670–85.

10.48047/jocaaa.2024.33.08.502

- [58] Jiang J-D, Lin T-C, Phoong S-M. New subspace-based blind channel estimation for orthogonally coded MIMO-OFDM systems. *Proc. IEEE ICASSP 2014*:6489–93.
- [59] Zhang W, Gao F, Yin Q. Blind channel estimation for MIMO-OFDM systems with low order signal constellation. *IEEE Commun. Lett.* 2015;19(3):499–502.
- [60] Yang H, Marzetta TL. Performance of conjugate and zero forcing beamforming in large-scale antenna systems. *IEEE J. Sel. Areas Commun.* 2013;31(2):172–9.
- [61] Hoydis J, ten Brink S, Debbah M. Massive MIMO in the UL/DL of cellular networks: How many antennas do we need?. *IEEE J. Sel. Areas Commun.* 2013;31(2):160–71.
- [62] Khansefid A, Minn H. Achievable downlink rates of MRC and ZF precoders in massive MIMO with uplink and downlink pilot contamination. *IEEE Trans. Commun.* 2015;63(12):4849–64.
- [63] R.R. Müller, M. Vehkaperä, L. Cottatellucci, Blind pilot decontamination, in: *Proc. 17th Int. ITG Workshop Smart Antennas (WSA)*, 2013, pp. 1–6.
- [64] D. Neumann, M. Joham, W. Utschick, Suppression of pilot-contamination in massive MIMO systems, in: *Proc. IEEE 15th Int. Workshop Signal Process. Adv. Wireless Commun. (SPAWC)*, 2014, pp. 11–15.
- [65] Ghavami K, Naraghi-Pour M. Blind channel estimation and symbol detection for multi-cell massive MIMO systems by expectation propagation. *IEEE Trans. Wireless Commun* 2018;17(2):943–54.
- [66] Yin H, Gesbert D, Filippou M, Liu Y. A coordinated approach to channel estimation in large-scale multiple-antenna systems. *IEEE J. Sel. Areas Commun.* 2013;31(2):264–73.
- [67] H. Yin, D. Gesbert, M.C. Filippou, Y. Liu, Decontaminating pilots in massive MIMO systems, in: *Proc. IEEE Int. Conf. Commun. (ICC)*, 2013, pp. 3170–3175.
- [68] H. Wang, Z. Pan, J. Ni, C.-L. I, A spatial domain based method against pilot contamination for multi-cell massive MIMO systems, in: *Proc. 8th Int. ICST Conf. Commun. Netw. China (CHINACOM)*, Aug. 2013, pp. 218–222.
- [69] Zhang J, Zhang B, Chen S, Mu X, El-Hajjar M, Hanzo L. Pilot contamination elimination for large-scale multiple-antenna aided OFDM systems. *IEEE J. Sel. Topics Signal Process.* 2014;8(5):759–72.

10.48047/jocaaa.2024.33.08.502

- [70] X. Wautelet, C. Herzet, A. Dejonghe, J. Louveaux, and L. Vandendorpe, "Comparison of EM-based algorithms for MIMO channel estimation," *IEEE Trans. Commun.*, vol. 55, no. 1, pp. 216–226, Jan. 2007.
- [71] A. K. Jagannatham and B. D. Rao, "Whitening-rotation-based semi-blind MIMO channel estimation," *IEEE Trans. Signal Process.*, vol. 54, no. 3, pp. 861–869, Mar. 2006.
- [72] M. Abuthinien, S. Chen, and L. Hanzo, "Semi-blind joint maximum likelihood channel estimation and data detection for MIMO systems," *IEEE Signal Process. Lett.*, vol. 15, pp. 202–205, Nov. 2008.
- [73] T. L. Marzetta, "Noncooperative cellular wireless with unlimited numbers of base station antennas," *IEEE Trans. Wireless Commun.*, vol. 9, no. 11, pp. 3590–3600, Nov. 2010.
- [74] E. Dahlman, S. Parkvall, J. Skold, and P. Beming, *3G Evolution: HSPA and LTE For Mobile Broadband, 2nd edition*. Elsevier, 2008.
- [75] K. Shi, E. Serpedin, and P. Ciblat, "Decision-directed fine synchronization in OFDM systems," *IEEE Transactions on Communications*, vol. 53, no. 3, pp. 408–412, March 2005.
- [76] E. Karami and M. Shiva, "Decision-directed recursive least squares MIMO channels tracking," *EURASIP Journal on Wireless Communications and Networking*, vol. 2006, no. 1, p. 043275, 2006.
- [77] J. Choi, *Adaptive and Iterative Signal Processing in Communications*. Cambridge, U.K.: Cambridge Univ. Press, 2006.
- [78] X. Deng, A. M. Haimovich, and J. Garcia-Frias, "Decision directed iterative channel estimation for MIMO systems," in *2003 IEEE International Conference on Communications (ICC)*, vol. 4, May 2003, pp. 2326–2329 vol.4.
- [79] C. H. Aldana, E. de Carvalho, and J. M. Cioffi, "Channel estimation for multicarrier multiple input single output systems using the EM algorithm," *IEEE Trans. Signal Process.*, vol. 51, no. 12, pp. 3280–3292, Dec. 2003.
- [80] C. Komninakis, C. Fragouli, A. H. Sayed, and R. D. Wesel, "Multi-input multi-output fading channel tracking and equalization using Kalman estimation," *IEEE Transactions on Signal Processing*, vol. 50, no. 5, pp. 1065–1076, May 2002.
- [81] D. Tse and P. Viswanath, *Fundamentals of Wireless Communication*, Cambridge University Press, 2005.

10.48047/jocaaa.2024.33.08.502

- [82] D. W. Bliss, A. M. Chan, and N. B. Chang, "MIMO Wireless Communication Channel Phenomenology," IEEE Transactions on Antennas and Propagation, vol. 52, no. 8, pp. 2073–2082, Aug. 2004.